§211.100

- (c) Drug product containers and closures shall be clean and, where indicated by the nature of the drug, sterilized and processed to remove pyrogenic properties to assure that they are suitable for their intended use. Such depyrogenation processes shall be validated.
- (d) Standards or specifications, methods of testing, and, where indicated, methods of cleaning, sterilizing, and processing to remove pyrogenic properties shall be written and followed for drug product containers and closures.
- (e) Medical gas containers and closures *must meet the following requirements*—(1) Gas-specific use outlet connections. Portable cryogenic medical gas containers that are not manufactured with permanent gas use outlet connections (e.g., those that have been silver-brazed) must have gas-specific use outlet connections that are attached to the valve body so that they cannot be readily removed or replaced (without making the valve inoperable and preventing the containers' use) except by the manufacturer. For the purposes of this paragraph, the term "manufacturer"; cludes any individual or firm that fills high-pressure medical gas cylinders or cryogenic medical gas containers. For the purposes of this section, a "portable cryogenic medical gas container" is one that is capable of being transported and is intended to be attached to a medical gas supply system within a hospital, health care entity, nursing home, other facility, or home health care setting, or is a base unit used to fill small cryogenic gas containers for use by individual patients. The term does not include cryogenic containers that are not designed to be connected to a medical gas supply system, e.g., tank trucks, trailers, rail cars, or small cryogenic gas containers for use by individual patients (including portable liquid oxygen units as defined at §868.5655 of this chapter).
- (2) Label and coloring requirements. The labeling specified at §201.328(a) of this chapter must be affixed to the container in a manner that does not interfere with other labeling and such that it is not susceptible to becoming worn or inadvertently detached during normal use. Each such label as well as materials used for coloring medical gas

containers must be reasonably resistant to fading, durable when exposed to atmospheric conditions, and not readily soluble in water.

[43 FR 45077, Sept. 29, 1978, as amended at 73 FR 51932, Sept. 8, 2008; 81 FR 81697, Nov. 18, 2016]

Subpart F—Production and Process Controls

§ 211.100 Written procedures; devi-

- (a) There shall be written procedures for production and process control designed to assure that the drug products have the identity, strength, quality, and purity they purport or are represented to possess. Such procedures shall include all requirements in this subpart. These written procedures, including any changes, shall be drafted, reviewed, and approved by the appropriate organizational units and reviewed and approved by the quality control unit.
- (b) Written production and process control procedures shall be followed in the execution of the various production and process control functions and shall be documented at the time of performance. Any deviation from the written procedures shall be recorded and justified.

§211.101 Charge-in of components.

Written production and control procedures shall include the following, which are designed to assure that the drug products produced have the identity, strength, quality, and purity they purport or are represented to possess:

- (a) The batch shall be formulated with the intent to provide not less than 100 percent of the labeled or established amount of active ingredient.
- (b) Components for drug product manufacturing shall be weighed, measured, or subdivided as appropriate. If a component is removed from the original container to another, the new container shall be identified with the following information:
 - (1) Component name or item code;
 - (2) Receiving or control number;
- (3) Weight or measure in new container;